



CUSTOMER DRAWING NO.

REMARKS

Lubrication : Harmonic Drive Harmonic Grease SK-2
 Cross Roller Bearing Harmonic Grease 4B No.2
 Designing and/or Handling of Harmonic Drive Gears (Harmonic Actuators)
 has to comply with technical information shown in Harmonic Drive Catalog.

Rated Torque at 2000r/min	Limit for Repeated Peak Torque	Limit for Average Torque	Limit for Momentary Peak Torque
5.4 N·m	19 N·m	7.7 N·m	35 N·m

PROPRIETORSHIP
 This drawing (document) is the **PROPERTY** of Harmonic Drive Systems, Inc. and shall not be traced, otherwise copied or used for purposes other than agreed upon, nor communicated to any third party without written permission of Harmonic Drive Systems, Inc.

訂正 REV	A	来歴 DESCRIPTION	Correction of misdescription			設計 DESIGN	S.Momose	Oct-26-'12	タイトル TITLE	ASSEMBLY DRAWING	
仕様 SPEC						検図 VRFD	H.Tukahara	Oct-26-'12	製品名 ARTICLE	SHD-14-100-2UH-LW	
機械加工無記号公差	0	0.5	6	30	120	315	1000	備考 REMARKS	特記無き角はC0.2以下、すみの丸みはR0.4以下		
GENERAL TOLERANCE	±0.05	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	無記号表面 SURFACES MARKED EXCEPT AS NOTED	50S	25S	6.3S
図番 DWG No						DWG SIZE	A3	UNIT	mm	THIRD ANG	
本図は(株)ハーモニック・ドライブ・システムズの所有に係わるものです。許可なく第三者に見せたり、トレースその他の複写及び指定された用途以外には使用しないで下さい。						HARMONIC DRIVE SYSTEMS		INC TOKYO JAPAN		C2A4385 - A	