



Rated Torque at 2000r/min	353 N·m	Limit for Repeated Peak Torque	755 N·m	Limit for Average Torque	500 N·m	Limit for Momentary Peak Torque	1570 N·m
---------------------------	---------	--------------------------------	---------	--------------------------	---------	---------------------------------	----------

REMARKS

Lubrication : Harmonic Drive Harmonic Grease SK-1A
 Cross Roller Bearing Harmonic Grease 4B No.2
 Designing and/or Handling of Harmonic Drive Gears (Harmonic Actuators)
 has to comply with technical information shown in Harmonic Drive Catalog.

PROPRIETORSHIP
 This drawing (document) is the **PROPERTY** of Harmonic Drive Systems, Inc. and shall not be traced, otherwise copied or reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of Harmonic Drive Systems, Inc.

CUSTOMER DRAWING NO.

訂正 REV	仕様 SPEC	承認 DESCRIPTION	尺 SCALE	1:2	第三角 THIRD ANG	単位 UNIT	A3 mm	設計 DESIGN	S. Momose	Oct-30-'12	タイトル TITLE	ASSEMBLY DRAWING
0	0.5	6	30	120	315	1000	備考 REMARKS	検 CHECKED	H. Takahara	Oct-30-'12	製品名 ARTICLE	SHF-45-100-2UH-LW
1	0.5	6	30	120	315	1000	特記無き角はC0.2以下、寸法の丸みはRC.4以下	承認 APPROVED	T. Yamagishi	Oct-30-'12	図番 DWG No	C2A4215
1	±0.05	±0.1	±0.2	±0.3	±0.5	±1.2	無記号表面アラサ SURFACES MARKED EXCEPT AS NOTED					